


11/11/2019




-Arch Pickets

 $59\frac{3}{4}" [1518mm]$

0.0
LEVEL GROUND

48" [1220mm]

30" [762mm]



8" [203mm]

— PRE-PUNCHED RAILS
FOR PICKET INSERTION

CONCRETE FOOTINGS
BELOW FROST LINE

- Post Cap Options:

-Spear:

-Pyramid:

[mm]

Arrow Head
Picket Top

19 3/4" [502mm]-35 3/4"H
31 3/4" [806mm]-47 3/4"H
43 3/4" [1111mm]-59 3/4"H
53 3/4" [1365mm]-69 3/4"H
67 3/4" [1721mm]-83 3/4"H
79 3/4" [2026mm]-95 3/4"H
91 3/4" [2330mm]-107 3/4"H
103 3/4" [2635mm]-119 3/4"H

8" [203mm]

- Cold Formed Steel Tubing Exterior and Interior Galvalume Coating
- Chromate Conversion Coating
- Electrostatically Applied
- Thermally Bonded Polyester Powder Coating
- Minimum Film Thickness 2.5 mm
- E-coated up to 70"H

- 3" x 3" (76mm x 76mm) 14 Gauge
- Standard Post Spacing 102 1/2" (2604mm) O.C.
36"H to 70"H
- Standard Post Spacing 76" (1930mm) O.C.
84"H to 120"H

- 2 1/2" x 1 1/2" (64mm x 38mm) 14 Gauge

- 1 1/2" x 3/4" (36mm x 19mm) 16 Gauge

- 12 Gauge Stamped

- Stainless Steel

- 96" (2438mm) - 36"H to 70"H
- 69 1/2" (1765mm) - 84"H to 120"H

- Refer to Catalogue

- Refer to Catalogue
- Optional Gate Opening Available Upon Request
- Optional Lock Box Available

- High Gloss Black, Flat Black, Textured Black.

- White, Brown, Green

13371 COLERAINE DRIVE, BOLTON, ONTARIO, L7E 3B6, CANADA OFFICE (905) 857-1010
FAX (905) 857-9536 - TOLL FREE 1(866) 955-0355 - WWW.NUVOIRON.COM - EMAIL: INFO@NUVOIRON.COM